



PRECISION MARSHALL STEEL COMPANY
One Northpoint Court, Bolingbrook IL 60440
Toll Free: 1-800-258-2558 - www.pmsteel.com

GROUND FLAT TYPICAL MATERIAL CERTIFICATE

STANDARD INFORMATION

**** All ground flat stock supplied by Precision Marshall Steel complies with DFARS requirements that state certain specialty metals must be melted and produced in the US or a qualifying country.**

STANDARD CHEMICAL COMPOSITION

AISI / SAE	UNS	Carbon	Manganese	Silicon	Phosphorous (Max)	Sulfur (Max)	Chromium	Vanadium	Tungsten	Molybdenum
A2	T30102	.95/1.05	.40/.60	.20/.35	.025	.005	4.90/5.30	.15/.20	--	.90/1.10
O1	T31501	.90/1.00	1.00/1.15	.20/.35	.020	.020	.40/.60	.30 Max	.40/.60	--
S7	T41907	.48/.53	.50/.70	.20/.40	.035	.003	3.10/3.40	.20/.30	--	1.30/1.60
NT	G41420	.38/.46	.70/1.00	.15/.30	.035	.040	.80/1.15	-	--	.15/.25
D2	T30402	1.50/1.60	.20/.40	.20/.60	.030	.020	11.25/12.00	.80/1.00	--	.70/.80
LC	G10180	.15/.25	.60/.90	--	.040	.050	--	--	--	--
LC (Under .250")		.03/.25	.90 Max	--	.040	.050	--	--	--	--
440C	S44004	1.05	.40	.40	--	--	17.00	--	--	.40
410	S41000	.13	.05	.40	--	--	12.00	-	--	--
420	S42000	.46	.40	.40	--	--	13.00	.30	--	--
M2	T11302	.78 / 1.05	.15 / .40	.20 / .45	.03	.03	.20 / .45	1.75 / 2.20	5.50 / 6.75	4.50 / 5.50

SPECIFICATIONS

GRADE	AISI	SAE	ASTM	FEDERAL	HARDNESS BRINELL	MACHINABILITY RATING	SURFACE TOLERANCE AND SQUARENESS		
							Regular (in)	Oversize (in)	
A2	A-2	J-437	A681-08	QQ-T-570 Rev.C	200-235	65	Thick. 18-36	+/- .001	+ .010/+ .015
O1	O-1	J-437	A681-08	QQ-T-570 Rev.C	177-212	95	Thick. 72	+/- .002	
S7	S-7	J-437	A681-08	QQ-T-570 Rev.C	188-223	95	Width	+ .005/- .000	+ .010/+ .015
NT	4142	--	A-322	--	261-321	85	Length 18	+ .125/+ .250	+ .125/+ .250
D2	D-2	J-437	A681-08	QQ-T-570 Rev.C	220-255	50	Length 24	+ .1875/+ .375	+ .1875/+ .375
LC	C-1018	--	A1018	635	168 MAX	--	Length 36	+ .250/+ .500	+ .250/+ .500
440C	440C	--	A276-17	QQ-S-763	--	--	Length 72	+ .250/+ .750	+ .250/+ .750
410	410	--	A240	QQ-S-763	--	--	Squares	+/- .001	+ .010/+ .015
420	420	--	A276-17	QQ-S-763	--	--	Metric (mm)		
M2	M-2	--	A600	QQ-T-590	255 MAX	--	Thick.	+/- .0254	
							Length	+6.35 / +12.7	

Precision Marshall Steel Company hereby attests that ground flat stock items as supplied have been tested and certified to meet all of the standards and limitations for ground flat stock as set forth above.

Material is RoHs, REACH, and Conflict Mineral compliant. The letter confirming compliance can be found on our website or distributor portal.

Certified: Wendy Gabauer
Support Services

Date: 6/10/2022